

工作性能

使用抗磨液压油，油液粘度24cst时

系列	理论排量 mL/rev	转速 r/min	流量 L/min							输入功率 KW						
			P=0 MPa L/min	P=7 MPa L/min	P=14 MPa L/min	P=21 MPa L/min	P=24 MPa L/min	P=28 MPa L/min	P=32 MPa L/min	P=0.7 MPa KW	P=7 MPa KW	P=14 MPa KW	P=21 MPa KW	P=24 MPa KW	P=28 MPa KW	P=32 MPa KW
T7B-B02 T7BS-B02	5.8	1000	5.8	4.9	4.2	3.3	—	—	—	0.2	0.9	1.7	2.5	—	—	—
		1200	7.0	6.1	5.4	4.5	4.0	—	—	0.4	1.3	2.2	3.2	3.6	—	—
		1500	8.7	7.8	7.1	6.2	5.7	5.2	4.7	0.6	1.7	2.8	4.0	4.5	5.2	5.9
		1800	10.4	9.5	8.8	7.9	7.4	6.9	6.4	0.7	2.0	3.4	5.0	5.6	6.4	7.2
T7B-B03 T7BS-B03	9.8	1000	9.8	8.9	8.2	7.3	6.8	6.3	5.8	0.2	1.3	2.6	3.9	4.5	5.2	6.0
		1200	11.8	10.9	10.2	9.3	8.8	8.3	7.8	0.4	1.8	3.3	4.9	5.5	6.4	7.3
		1500	14.7	13.8	13.1	12.2	11.7	11.2	10.7	0.7	2.4	4.2	6.1	6.9	8.0	9.1
		1800	17.6	16.7	16.0	15.1	14.6	14.1	13.6	0.8	2.8	5.1	7.5	8.5	9.7	11.0
T7B-B04 T7BS-B04	12.8	1000	12.8	11.9	11.2	10.3	9.8	9.3	8.8	0.2	1.7	3.3	5.0	5.7	6.6	7.6
		1200	15.4	14.5	13.8	12.9	12.4	11.9	11.4	0.5	2.2	4.2	6.1	6.9	8.1	9.2
		1500	19.2	18.3	17.6	16.7	16.2	15.7	15.2	0.7	2.9	5.3	7.7	8.7	10.1	11.5
		1800	23.0	22.1	21.4	20.5	20.0	19.5	19.0	0.9	3.4	6.4	9.4	10.6	12.3	13.9
T7B-B05 T7BS-B05	15.9	1000	15.9	15.0	14.3	13.4	12.9	12.4	11.9	0.3	2.1	4.1	6.0	6.9	8.1	9.2
		1200	19.1	18.2	17.5	16.6	16.1	15.6	15.1	0.5	2.7	5.0	7.4	8.4	9.8	11.2
		1500	23.9	23.0	22.3	21.4	20.9	20.4	19.9	0.8	3.4	6.4	9.3	10.6	12.3	14.0
		1800	28.6	27.7	27.0	26.1	25.6	25.1	24.6	0.9	4.1	7.7	11.3	12.8	14.9	16.9
T7B-B06 T7BS-B06	19.8	1000	19.8	18.9	18.2	17.3	16.8	16.3	15.8	0.3	2.5	5.0	7.4	8.5	9.9	11.3
		1200	23.8	22.9	22.2	21.3	20.8	20.3	19.8	0.6	3.2	6.1	9.1	10.3	12.0	13.7
		1500	29.7	28.8	28.1	27.2	26.7	26.2	25.7	0.8	4.1	7.7	11.4	12.9	15.0	17.1
		1800	35.6	34.7	34.0	33.1	32.6	32.1	31.6	1.0	4.9	9.3	13.8	15.7	18.1	20.6
T7B-B07 T7BS-B07	22.5	1000	22.5	21.6	20.9	20.0	19.5	19.0	18.5	0.4	2.8	5.6	8.3	9.6	11.2	12.8
		1200	27.0	26.1	25.4	24.5	24.0	23.5	23.0	0.6	3.6	6.9	10.2	11.6	13.5	15.4
		1500	33.8	32.9	32.2	31.3	30.8	30.3	29.8	0.9	4.6	8.7	12.8	14.6	16.9	19.3
		1800	40.5	39.6	38.9	38.0	37.5	37.0	36.5	1.1	5.5	10.5	15.5	17.6	20.4	23.2
T7B-B08 T7BS-B08	24.9	1000	24.9	24.0	23.3	22.4	21.9	21.4	20.9	0.4	3.1	6.2	9.2	10.5	12.3	14.0
		1200	29.9	29.0	28.3	27.4	26.9	26.4	25.9	0.6	3.9	7.6	11.2	12.8	14.8	16.9
		1500	37.4	36.5	35.8	34.9	34.4	33.9	33.4	0.9	5.0	9.5	14.1	16.0	18.6	21.2
		1800	44.8	43.9	43.2	42.3	41.8	41.3	40.8	1.1	6.0	11.5	17.0	19.3	22.4	25.5
T7B-B10 T7BS-B10	31.8	1000	31.8	30.9	30.2	29.3	28.8	28.3	27.8	0.5	3.9	7.8	11.6	13.3	15.5	17.7
		1200	38.2	37.3	36.6	35.7	35.2	34.7	34.2	0.7	4.9	9.5	14.1	16.1	18.7	21.4
		1500	47.7	46.8	46.1	45.2	44.7	44.2	43.7	1.1	6.2	11.9	17.7	20.1	23.4	26.7
		1800	57.2	56.3	55.6	54.7	54.2	53.7	53.2	1.3	7.4	14.4	21.3	24.3	28.2	32.1
T7B-B12 T7BS-B12	41.0	1000	41.0	40.1	39.4	38.5	38.0	37.5	—	0.6	5.0	9.9	14.8	17.0	19.8	—
		1200	49.2	48.3	47.6	46.7	46.2	45.7	—	0.9	6.2	12.1	18.0	20.5	23.9	—
		1500	61.5	60.6	59.9	59.0	58.5	58.0	—	1.2	7.8	15.2	22.5	25.7	29.9	—
		1800	73.8	72.9	72.2	71.3	70.8	70.3	—	1.5	9.4	18.2	27.1	30.9	35.9	—
T7B-B15 T7BS-B15	50.0	1000	50.0	49.1	48.4	47.5	47.0	46.5	—	0.7	6.0	12.0	18.0	20.6	24.0	—
		1200	60.0	59.1	58.4	57.5	57	56.5	—	1.0	7.4	14.6	21.7	24.8	28.9	—
		1500	75.0	74.1	73.4	72.5	72.0	71.5	—	1.4	9.4	18.3	27.2	31.1	36.2	—
		1800	90.0	89.1	88.4	87.5	87.0	86.5	—	1.7	11.3	22.0	32.8	37.4	43.5	—

工作性能

使用抗磨液压油，油液粘度24cst时

系列	理论排量 mL/rev	转速 r/min	流量 L/min							输入功率 KW						
			P=0 MPa L/min	P=7 MPa L/min	P=14 MPa L/min	P=21 MPa L/min	P=24 MPa L/min	P=28 MPa L/min	P=0 MPa KW	P=7 MPa KW	P=14 MPa KW	P=21 MPa KW	P=24 MPa KW	P=28 MPa KW	P=0 MPa KW	P=28 MPa KW
T6C-003 T6C-B03	10.8	1000	10.8	8.3	5.8	—	—	—	0.9	2.2	3.7	—	—	—	—	—
		1200	13.0	10.5	8.0	—	—	—	1.1	2.6	4.4	—	—	—	—	—
		1500	16.2	13.7	11.2	8.7	8.2	—	1.3	3.3	5.4	7.6	8.5	—	—	—
		1800	19.4	16.9	14.4	11.9	11.4	10.3	1.7	4.0	6.4	8.9	10.0	11.5	—	—
T6C-005 T6C-B05	17.2	1000	17.2	14.7	12.2	9.7	9.2	—	1.0	3.0	5.2	7.4	8.4	—	—	—
		1200	20.6	18.1	15.6	13.1	12.6	11.5	1.1	3.5	6.2	8.8	10.0	11.5	—	—
		1500	25.8	23.3	20.8	18.3	17.8	16.7	1.4	4.4	7.7	10.9	12.3	14.1	—	—
		1800	31.0	28.5	26.0	23.5	23.0	21.9	1.9	5.3	9.1	13.0	14.6	16.8	—	—
T6C-006 T6C-B06	21.3	1000	21.3	18.8	16.3	13.8	13.3	12.2	1.0	3.4	6.1	8.9	10.0	11.5	—	—
		1200	25.6	23.1	20.6	18.1	17.6	16.5	1.2	4.1	7.3	10.5	11.9	13.8	—	—
		1500	32.0	29.5	27.0	24.5	24.0	22.9	1.5	5.1	9.1	13.1	14.8	17.0	—	—
		1800	38.3	35.8	33.3	30.8	30.3	29.2	1.9	6.2	10.8	15.6	17.6	20.3	—	—
T6C-008 T6C-B08	26.4	1000	26.4	23.9	21.4	18.9	18.4	17.3	1.1	4.0	7.3	10.6	12.0	13.9	—	—
		1200	31.7	29.2	26.7	24.2	23.7	22.6	1.3	4.8	8.7	12.7	14.4	16.6	—	—
		1500	39.6	37.1	34.6	32.1	31.6	30.5	1.6	6.0	10.9	15.8	17.8	20.6	—	—
		1800	47.5	45.0	42.5	40.0	39.5	38.4	2.1	7.2	13.0	18.8	21.3	24.6	—	—
T6C-010 T6C-B10	34.1	1000	34.1	31.6	29.1	26.6	26.1	25.0	1.2	4.9	9.1	13.3	15.1	17.5	—	—
		1200	40.9	38.4	35.9	33.4	32.9	31.8	1.4	5.9	10.9	15.9	18.1	20.9	—	—
		1500	51.2	48.7	46.2	43.7	43.2	42.1	1.7	7.3	13.6	19.8	22.5	26.0	—	—
		1800	61.4	58.9	56.4	53.9	53.4	52.3	2.2	8.9	16.2	23.6	26.8	31.0	—	—
T6C-012 T6C-B12	37.1	1000	37.1	34.6	32.1	29.6	29.1	28.0	1.2	5.3	9.8	14.4	16.3	18.9	—	—
		1200	44.5	42.0	39.5	37.0	36.5	35.4	1.4	6.3	11.7	17.2	19.5	22.6	—	—
		1500	55.7	53.2	50.7	48.2	47.7	46.6	1.7	7.9	14.6	21.4	24.3	28.1	—	—
		1800	66.8	64.3	61.8	59.3	58.8	57.7	2.3	9.5	17.5	25.5	29.0	33.6	—	—
T6C-014 T6C-B14	46.0	1000	46.0	43.5	41.0	38.5	38.0	36.9	1.3	6.3	11.9	17.5	19.9	23.1	—	—
		1200	55.2	52.7	50.2	47.7	47.2	46.1	1.5	7.6	14.2	20.9	23.8	27.6	—	—
		1500	69.0	66.5	64.0	61.5	61.0	59.9	1.9	9.4	17.7	26.1	29.6	34.3	—	—
		1800	82.8	80.3	77.8	75.3	74.8	73.7	2.5	11.4	21.2	31.1	35.4	41.0	—	—

工作性能

使用抗磨液压油，油液粘度24cst时

系列	理论排量 mL/rev	转速 r/min	流量 L/min						输入功率 KW					
			P=0 MPa L/min	P=7 MPa L/min	P=14 MPa L/min	P=21 MPa L/min	P=24 MPa L/min	P=28 MPa L/min	P=0 MPa KW	P=7 MPa KW	P=14 MPa KW	P=21 MPa KW	P=24 MPa KW	P=28 MPa KW
T6C-017 T6C-B17	58.3	1000	58.3	55.8	53.3	50.8	50.3	49.2	1.5	7.8	14.8	21.8	24.8	28.8
		1200	70.0	67.5	65.0	62.5	62.0	60.9	1.7	9.3	17.7	26.1	29.7	34.5
		1500	87.5	85.0	82.5	80.0	79.5	78.4	2.1	11.6	22.0	32.5	37.0	42.9
		1800	104.9	102.4	99.9	97.4	96.9	95.8	2.7	13.9	26.4	38.9	44.2	51.4
T6C-020 T6C-B20	63.8	1000	63.8	61.3	58.8	56.3	55.8	54.7	1.5	8.4	15.8	23.7	27.0	31.4
		1200	76.6	74.1	71.6	69.1	68.6	67.5	1.8	10.0	19.2	28.4	32.3	37.6
		1500	95.7	93.2	90.7	88.2	87.7	86.6	2.2	12.5	24.0	35.4	40.3	46.8
		1800	114.8	112.3	109.8	107.3	106.8	105.7	2.8	15.1	28.7	42.3	48.2	56.0
T6C-022 T6C-B22	70.3	1000	70.3	67.8	65.3	62.8	62.3	61.2	1.6	9.2	17.6	26.0	29.6	34.4
		1200	84.4	81.9	79.4	76.9	76.4	75.3	1.9	11.0	21.0	31.1	35.5	41.2
		1500	105.5	103.0	100.5	98.0	97.5	96.4	2.3	13.7	26.2	38.8	44.2	51.3
		1800	126.5	124.0	121.5	119.0	118.5	117.4	3.0	16.5	31.4	46.4	52.9	61.5
T6C-025 T6C-B25	79.3	1000	79.3	76.8	74.3	71.8	71.3	70.2	1.7	10.2	19.7	29.2	33.2	38.6
		1200	95.2	92.7	90.2	87.7	87.2	86.1	2.0	12.2	23.6	34.9	39.8	46.3
		1500	119.0	116.5	114.0	111.5	111.0	109.9	2.5	15.2	29.4	43.5	49.6	57.6
		1800	142.7	140.2	137.7	135.2	134.7	133.6	3.2	18.4	35.2	52.1	59.3	69.0
T6C-028* T6C-B28	88.8	1000	88.8	86.3	83.8	81.3			1.8	11.3	21.9	32.5		
		1200	106.6	104.1	101.6	99.1			2.1	13.5	26.2	38.9		
		1500	133.2	130.7	128.2	125.7			2.7	16.9	32.7	48.5		
		1800	159.8	157.3	154.8	152.3			3.4	20.3	39.2	58.1		
T6C-031* T6C-B31	100.0	1000	100.0	97.5	95.0	92.5			2.0	12.6	24.5	36.4		
		1200	120.0	117.5	115.0	112.5			2.3	15.1	29.4	43.6		
		1500	150.0	147.5	145.0	142.5			2.9	18.9	36.6	54.4		
		1800	180.0	177.5	175.0	172.5			3.6	22.7	43.9	65.1		

*28、31:最大间歇压力21MPa
-因为内泄大于理论值的50%,故没有应用。

工作性能

使用抗磨液压油，油液粘度24cst时

系列	理论排量 mL/rev	转速 r/min	流量 L/min					输入功率 KW				
			P=0 MPa L/min	P=7 MPa L/min	P=14 MPa L/min	P=21 MPa L/min	P=24 MPa L/min	P=0 MPa KW	P=7 MPa KW	P=14 MPa KW	P=21 MPa KW	P=24 MPa KW
T6D-014 T6D-B14	47.6	1000	47.6	43.6	38.6	34.6	32.6	1.6	6.8	12.5	18.3	20.7
		1200	57.1	53.1	48.1	44.1	42.1	1.8	8.0	14.9	21.8	24.8
		1500	71.4	67.4	62.4	58.4	56.4	2.3	10.0	18.5	27.0	30.7
		1800	85.7	81.7	76.7	72.7	70.7	2.9	12.1	22.3	32.5	36.9
T6D-017 T6D-B17	58.2	1000	58.2	54.2	49.2	45.2	43.2	1.7	8.0	15.0	22.0	25.0
		1200	69.8	65.8	60.8	56.8	54.8	1.9	9.5	17.9	26.3	29.9
		1500	87.3	83.3	78.3	74.3	72.3	2.5	11.8	22.2	32.6	37.0
		1800	104.8	100.8	95.8	91.8	89.8	3.1	14.4	26.8	39.2	44.5
T6D-020 T6D-B20	66.0	1000	66.0	62.0	57.0	53.0	51.0	1.8	8.9	16.8	24.7	28.1
		1200	79.2	75.2	70.2	66.2	64.2	2.1	10.6	20.1	29.6	33.6
		1500	99.0	95.0	90.0	86.0	84.0	2.7	13.2	24.9	36.7	41.7
		1800	118.8	114.8	109.8	105.8	103.8	3.3	16.0	30.1	44.1	50.1
T6D-024 T6D-B24	79.5	1000	79.5	75.5	70.5	66.5	64.5	1.9	10.5	20.0	29.4	33.5
		1200	95.4	91.4	86.4	82.4	80.4	2.2	12.5	23.9	35.2	40.1
		1500	119.3	115.3	110.3	106.3	104.3	2.9	15.6	29.7	43.7	49.8
		1800	143.1	139.1	134.1	130.1	128.1	3.6	18.8	35.7	52.6	59.9
T6D-028 T6D-B28	89.7	1000	89.7	85.7	80.7	76.7	74.7	2.0	11.7	22.3	33.0	37.5
		1200	107.6	103.6	98.6	94.6	92.6	2.4	13.9	26.7	39.5	45.0
		1500	134.6	130.6	125.6	121.6	119.6	3.1	17.4	33.2	49.1	55.9
		1800	161.5	157.5	152.5	148.5	146.5	3.8	21.0	40.0	59.0	67.2
T6D-031 T6D-B31	98.3	1000	98.3	94.3	89.3	85.3	83.3	2.1	12.7	24.3	36.0	41.0
		1200	118.0	114.0	109.0	105.0	103.0	2.5	15.1	29.1	43.1	49.1
		1500	147.5	143.5	138.1	131.9	127.3	3.2	18.9	36.2	53.6	61.0
		1800	176.9	172.9	167.9	163.9	161.9	4.0	22.8	43.6	64.5	73.4
T6D-035 T6D-B35	111.0	1000	111.0	107.0	102.0	98.0	96.0	2.3	14.2	27.3	40.5	46.1
		1200	133.2	129.2	124.2	120.2	118.2	2.7	16.9	32.7	48.5	55.2
		1500	166.5	162.5	157.5	153.5	151.5	3.4	21.1	40.7	60.3	68.7
		1800	199.8	195.8	190.8	186.8	184.8	4.2	25.4	49.0	72.5	82.5
T6D-038 T6D-B38	120.3	1000	120.3	116.3	111.3	107.3	105.3	2.4	15.2	29.5	43.7	49.8
		1200	144.4	140.4	135.4	131.4	129.4	2.8	18.2	35.3	52.4	59.7
		1500	180.5	176.5	171.5	167.5	165.5	3.6	22.7	43.9	65.2	74.3
		1800	216.5	212.5	207.5	203.5	201.5	4.4	27.4	52.9	78.3	89.2
T6D-042 T6D-B42	136.0	1000	136.0	132.0	127.0	123.0	121.0	2.6	17.1	33.1	49.2	56.1
		1200	163.2	159.2	154.2	150.2	148.2	3.0	20.4	39.7	59.0	67.2
		1500	204.0	200.0	195.0	191.0	189.0	3.9	25.5	49.4	73.4	83.7
		1800	244.8	240.8	235.8	231.8	229.8	4.8	30.7	59.5	88.2	100.5
T6D-45 T6D-B45	145.7	1000	145.7	141.7	136.7	132.7	130.7	2.7	18.2	35.4	52.6	59.9
		1200	174.8	170.8	165.8	161.8	159.8	3.2	21.7	42.4	63.0	71.9
		1500	218.6	214.6	209.6	205.6	203.6	4.0	27.2	52.8	78.5	89.5
		1800	262.3	258.3	253.3	249.3	247.3	5.0	32.7	63.5	94.3	107.5
* T6D-050 T6D-B50	158.0	1000	158.0	154.0	149.0	145.0	—	2.8	19.6	38.3	56.9	—
		1200	189.6	185.6	180.6	176.6	—	3.3	23.5	45.8	68.2	—
		1500	237.0	233.0	228.0	224.0	—	4.3	29.3	57.1	85.0	—
		1800	284.4	280.4	275.4	271.4	—	5.2	35.3	68.7	102.1	—
*T6D-061	190.5	1500	285.7	281.7	278.0	—	—	4.6	35.0	60.6	—	—

*50:最大间歇压力21MPa*61:最大间歇压力12MPa*

工作性能

使用抗磨液压油，油液粘度24cst时

系列	理论排量 mL/rev	转速 r/min	流量 L/min			输入功率 KW		
			P=0 MPa L/min	P=14 MPa L/min	P=30 MPa L/min	P=0 MPa KW	P=14 MPa KW	P=30 MPa KW
T7D-B14 T7DS-B14	44.0	1500	66.0	59.4	51.9	1.5	16.6	34.2
		1800	79.1	72.5	64.9	2.6	20.7	43.6
T7D-B17 T7DS-B17	55.0	1500	82.5	75.9	68.4	1.7	20.4	42.4
		1800	98.8	92.3	84.7	2.8	25.3	53.6
T7D-B20 T7DS-B20	66.0	1500	99.0	92.4	84.9	1.9	24.3	50.7
		1800	118.6	112.0	104.5	3.0	29.8	63.6
T7D-B22 T7DS-B22	70.3	1500	105.5	98.8	91.3	2.0	25.8	53.9
		1800	126.4	119.8	112.3	3.1	31.6	67.6
T7D-B24 T7DS-B24	81.1	1500	121.7	115.0	107.5	2.2	29.5	62.0
		1800	145.8	139.2	131.6	3.4	36.1	77.4
T7D-B28 T7DS-B28	90.0	1500	135.0	128.4	120.9	2.3	32.7	68.7
		1800	161.8	155.2	147.6	3.5	39.7	85.5
T7D-B31 T7DS-B31	99.2	1500	197.2	142.2	134.7	2.5	35.9	75.6
		1800	178.3	171.7	164.2	3.7	43.6	93.7
T7D-B35* T7DS-B35	113.4	1500	170.1	163.5	156.9	2.7	40.8	80.5
		1800	203.9	197.2	190.6	4.0	49.4	97.2
T7D-B38* T7DS-B38	120.6	1500	180.9	174.3	167.7	2.9	43.4	85.6
		1800	216.8	210.2	203.6	4.2	52.4	103.2
T7D-B42* T7DS-B42	137.5	1500	206.3	199.6	194.0	3.2	49.3	90.5
		1800	247.2	240.6	234.9	4.5	59.4	111.4
T7D-045* T7D-B45 T7DS-045 T7DS-B45	145.7	1500	218.6	209.2	202.6	4.1	52.8	89.5
		1800	262.0	253.6	247.5	5.0	62.4	107.7
T7D-050* T7D-B50 T7DS-050 T7DS-B50	158.0	1500	237.0	227.7	223.0	4.4	57.1	85.0
		1800	284.0	275.8	271.3	5.3	67.5	100.3

* B35-B38:最大间歇压力28MPa * B42 :最大间歇压力26MPa
* 45 :最大间歇压力24MPa * 50 :最大间歇压力21MPa

工作性能

使用抗磨液压油，油液粘度24cst时

系列	理论排量 mL/rev	转速 r/min	流量 L/min					输入功率 KW				
			P=0 MPa L/min	P=7 MPa L/min	P=14 MPa L/min	P=21 MPa L/min	P=24 MPa L/min	P=0 MPa KW	P=7 MPa KW	P=14 MPa KW	P=21 MPa KW	P=24.5 MPa KW
T6E-042	132.3	1000	132.3	127.3	122.3	117.3	115.3	3.3	17.4	33.0	48.5	55.2
		1200	158.8	153.8	148.8	143.8	141.8	4.0	20.8	39.5	58.3	66.3
		1500	198.5	193.5	188.5	183.5	181.5	5.2	26.2	49.4	72.7	82.7
		1800	238.1	233.1	228.1	223.1	221.1	6.4	31.5	59.4	87.3	99.4
T6E-045	142.4	1000	142.4	137.4	132.4	127.4	125.4	3.5	18.6	35.3	52.1	59.3
		1200	170.9	165.9	160.9	155.9	153.9	4.1	22.2	42.4	62.5	71.2
		1500	213.6	208.6	203.6	198.6	196.6	5.4	27.9	52.9	78.0	88.8
		1800	256.3	251.3	246.3	241.3	239.3	6.6	33.6	63.7	93.7	106.6
T6E-050	158.5	1000	158.5	153.5	148.5	143.5	141.5	3.6	20.4	39.1	57.7	65.7
		1200	190.2	185.2	180.2	175.2	173.2	4.3	24.5	46.9	69.3	78.9
		1500	237.8	232.8	227.8	222.8	220.8	5.7	30.7	58.6	86.5	98.4
		1800	285.3	280.3	275.3	270.3	268.3	6.9	37.0	70.4	103.9	118.2
T6E-052	164.8	1000	164.8	159.8	154.8	149.8	147.8	3.7	21.2	40.6	59.9	68.2
		1200	197.8	192.8	187.8	182.8	180.8	4.4	25.4	48.6	71.9	81.9
		1500	247.2	242.2	237.2	232.2	230.2	5.8	31.8	60.8	89.8	102.2
		1800	296.6	291.6	286.6	281.6	279.6	7.1	38.3	73.1	107.8	122.8
T6E-057	179.8	1000	179.8	174.8	169.8	164.8	162.8	3.9	22.9	44.1	65.2	74.2
		1200	215.8	210.8	205.8	200.8	198.8	4.6	27.5	52.8	78.2	89.1
		1500	269.7	264.7	259.7	254.7	252.7	6.0	34.5	66.0	97.6	111.2
		1800	323.6	318.6	313.6	308.6	306.6	7.4	41.5	79.4	117.3	133.6
T6E-062	196.7	1000	196.7	191.7	186.7	181.7	179.7	4.1	24.9	48.0	71.1	81.0
		1200	236.0	231.0	226.0	221.0	219.0	4.9	29.8	57.6	85.3	97.2
		1500	295.1	290.1	285.1	280.1	278.1	6.3	37.4	71.9	106.5	121.3
		1800	354.1	349.1	344.1	339.1	337.1	7.7	45.0	86.5	127.9	145.7
T6E-066	213.3	1000	213.3	208.3	203.3	198.3	196.3	4.3	26.8	51.9	76.9	87.6
		1200	256.0	251.0	246.0	241.0	239.0	5.1	32.2	62.2	92.3	105.2
		1500	320.0	315.0	310.0	305.0	303.0	6.6	40.3	77.8	115.2	131.3
		1800	383.9	378.9	373.9	368.9	366.9	8.1	48.5	93.4	138.4	157.7
T6E-072	227.1	1000	227.1	222.0	217.1	212.1	210.1	4.4	28.4	55.1	81.7	93.1
		1200	272.5	267.5	262.5	257.5	255.5	5.3	34.1	66.1	98.1	111.8
		1500	340.7	335.7	330.7	325.7	323.7	6.9	42.7	82.6	122.5	139.6
		1800	408.8	403.8	398.8	393.8	391.8	8.4	51.4	99.2	147.1	167.6
T6E-085*	269	1000	269.0	264.0	—	—	—	4.9	33.3	—	—	—
		1200	322.8	317.8	—	—	—	5.9	40.0	—	—	—
		1500	403.5	398.5	—	—	—	7.6	50.1	—	—	—
		1800	484.2	479.2	—	—	—	9.2	60.2	—	—	—

* 85 :最大转速2000r/min，最大间歇压力9MPa